

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	17.05.08	NEW DRAWING	







SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°C to +105°C

Contact Material:Phosphor Bronze
Contact Plating:Tin Plated
Insulator Material:Polyester(UL94V-0)
Standard: LCP
Max.Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)

Ordering Information

5920 - M XX M XX B X X 01

Type
FFemale
MMale
No.of
Pins
6~26
Contact Plating
SN:tin
G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:30U"Gold
S0:Gold Flash/Tin
SM:Matte-Tin
Color
B:Black
W:White
Post
W:With Post
N:W/O Post
Packing
0=Pe bag
A=1Troy
T=Tube
P=Tube+Cap
R=Reel+Cap
M=Mylar+Reel



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

TSINGRE SHENZHEN TSINGRE TECHNOLOGY CO.,LTD
www.tsingre.com

DRAW	David	OPERATION	SCALE	NIS	TITLE: 1.27 Picoflex Header Male Connector SMT Type
CHECK	Jose	X.XX X.XXX Angle	UNIT mm	SIZE A4	PRODUCT CUSTOMER DRAWING
APPROVE	Hey	±0.30 ±0.20 ±0.10 ±3°	PART NO. 5920-MXXMXXBX01	DOC PART 001	REVISION A0
			CUSTOMER PART NO.	CUSTOMER	SHEET NUMBER 1 OF 1